



octagreen

Exterior Coating

Octagreen Nano Products India (P) Ltd., Elamakkara,
Cochin -682 026 Ph: 0484 2539439, Mob: 8590041004



octagreen

Superior technology, for the best results

The future in paints is here, today! Octagreen invites you to the breath-taking world of superior technology based paints. Paints that usher in a rare, lasting class and character to your exteriors and interiors. Not only that. Being classified as 'Green Paints', the Octagreen range of paints are absolutely environmentally friendly and conform to global 'green' standards.

Taking origin in the 3rd generation green technology, Octagreen paints bring you the best of best in range of colours, elegance and economy. Developed by world-renowned scientists, the Octagreen paints range display exceptional dispersion characteristics, due to their ordered molecule structures.

The water-base range has low VOC and display exceptional anti-fungal/bacteria/algae, hydro-phobic, UV resistance, heat insulation with elastomeric (stretchable to cover cracks) properties. Thus making them the ideal choice for interiors & exteriors.

The select Octagreen range also include transparent coatings for plaster, glass, ceramic, with excellent water repellent, anti-bacteria/fungal and non-polymeric properties.

Come. Choose your favourite colour. While choosing lasting grandeur to your buildings, you're doing a lot to help preserve nature too!



Exterior Coating Solutions



ULTRA GUARD Waterproof Exterior Emulsion

Ultra Guard Waterproof Elastomeric Exterior Emulsion with crack-bridging property is a protective coat in all weather conditions.



ALL WEATHER Weatherproof Exterior Emulsion

All Weather Weatherproof Exterior Emulsion is a water based, highly modified acrylic emulsion which prevents moss and algae growth and is ideal for extreme climatic conditions.



AURA Superior Exterior Emulsion

Aura Superior Exterior Emulsion is a high performing acrylic emulsion with supreme quality in economy range.



FIRST COAT Exterior Primer

Alkali Resistant Anti-efflorescent Exterior Primer

Directions for Use (Exterior)

- Cleaning:** Ensure that the surface to be painted is free from any loose paint, dirt, grease or dampness or seepage. Any previous growth of fungus, algae, or moss to be removed thoroughly by vigorous wire brushing and cleaning with water.
- Primer:** Freshly plastered surface should be allowed to cure completely. For both fresh and repainted surface, apply one coat of Octagreen's First Coat Exterior Primer by recommended thinning with water. Allow the primer coat to dry for 4 hrs.
- Topcoat:** Apply 2-3 coats by diluting 1lit., with maximum 400 ml. of clean water. A gap of 4-6 hrs should be given between the coats. Ensure that horizontal surface like top of windows, ledges, etc., are painted with one additional coat. Ultraguard has been formulated to be applied as package consistency. Dilution if required with maximum 300ml. of clean water.

Directions for Use (Primer)

- Surface preparation:** Remove paint/dirt/loose particles from the surface to be painted, using wire brush or sand papers. Cracks to be filled with crack filler.
- Application:** Thin 1 ltr. Primer with upto 1 ltr. of water, depending on required consistency. Apply one coat with brush/roller and allow to dry for 6-8 hrs. Apply an additional coat if required.

No added Lead, Mercury, Arsenic & Chromium

For special application instructions, contact our customer care.

